


INT276 LCF®



The optical level monitoring INT276 LCF is employed for contactless single point measurement of fluid levels, e.g. on compressors, pumps, tanks, etc. The solution consists of a screw-in part and an evaluation unit. The screw-in part for optical level monitoring is permanently built-in at the measuring point. The electronic evaluation unit can be mounted or replaced without opening the circuit of the medium to be monitored.




Light pulses of the device are refracted in fluids and reflected in gaseous environments. This allows the INT276 LCF to detect the fluid level reliably.

Time-delayed reaction prevents switching errors that can be caused by temporary fluctuations of the fluid.

Once the correct level has been reached again or the error has been rectified, the relay energises again.

An integrated own monitoring system ensures high reliability; an installation check monitors the proper assembly.

Level good, no fault

-  Level good, no fault
 Level missing
 Internal error, voltage supply too low or faulty assembly

1. Ensure cleanliness of thread and glass of the screw-in part.

2. Mount evaluation unit into the screw-in part. The cable outlet has to point downwards here.
3. Tighten the coupling ring hand tight.



The mounting, maintenance and operation are to be carried out by an electrician. The valid European and national standards for connecting electrical equipment have to be observed.

See back side for further specifications

INT276 LCF® Level monitor

INT276 LCF®

Technical specifications

Supply voltage	
- 52 S 476 ...	AC 50/60Hz 230V $\pm 10\%$ 3VA
- 41 S 476 ...	AC 50/60Hz 115V $\pm 10\%$ 3VA
Permitted ambient temperature	-30...+60°C
Medium temperature	Max. +120°C (<1h) Max. +100°C
Permitted rel. humidity	10-95% r. h. no condensation
Switch delay	
- After applying the supply voltage	3s ± 1 s
- Level missing or fault	5s ± 2 s
- Level good and no fault	5s ± 2 s
Relay	
- Contact	AC 240V 2.5A C300 at least AC/DC 100mV 0.5mA
- Mechanical service life	Approx. 1 million switching cycles
Protection class acc. to EN 60529	IP54 in mounted condition
Connection type	Cable 5 x AWG 18/7 L=1m
Housing material	PA glass-fibre-reinforced
Mounting	Union nut (torque max. 10Nm)
Dimensions	Refer to dimensions in mm
Weight	Approx. 160g
Check base	EN 61000-6-2, EN 61000-6-3 EN 61010-1 Overvoltage category II Pollution level 2
Approval	UL File No. E222056 cURus

Order data

INT276 LCF Level monitor (AC 230V)	52 S 476 S61
INT276 LCF Level monitor (AC 115V)	41 S 476 S61
Accessories and application Information	see www.kriwan.com