# Industrial Experience

# 行业经验

# Rice cooker series 电饭煲系列(食品加工设备和烹饪设备)



#### Type: TXW-060 Features:

Fast response and stable performance in temp. measurement. Applications: IH rice cooker, IH high pressure cooker.

Temperature Range: -40°C ~ 200°C

Thermal time constant : Less than 10sec. (on hot plate ) 类型:**TXW-060** 特点: 快速响应型,感温一致性好。

用途: H智能电坂煲、IH电压力锅。 使用温度范围: -40℃-200℃ 熟时间常数: <10秒 (熱平板)



Type: **TXW-061** Features: Temp. sensor with built-in thermal fuse. Applications: IH cookers. Temperature Range: -40°C - 200°C

-40°C ~ 200°C Thermal time constant : Less than 20sec. (on hot plate )

#### 类型:TXW-061

特点: 内置温度保险丝的复合温度传感器。 用途: 川料理器及电饭煲等用。 使用温度范围: -40℃-200℃ 热时间常数: 小于20秒(热平板)



#### Type: TXW-061 Features: Temp. sensor with built-in thermal fuse.

Applications: IH cookers.

Temperature Range: -40°C - 200°C

Thermal time constant : Less than 10sec. (on hot plate)

### 类型:TXW-061

特点: 内置温度保险丝的复合温度传感器。 用途: IH科理器及电饭煲等用。 使用温度范围: -40℃-200℃ 熱时间常数: 小于10秒(热平板)

# Rice cooker series 电饭煲系列(食品加工设备和烹饪设备)



# Type: TXW-063

Features: Stainless steel encapsulated sensor with epoxy sealed. Available for earth wire assembling.

Applications: IH cookers. Temperature Range: -10°C ~ 200°C

Thermal time constant : Less than 8sec. (in steam)

## 类型:TXW-063

特点: 不锈钢结构的温度传感器,环氧树脂防渗 透封装,可安装接地线。

用途: □□料理器及电饭煲锅顶温度传感器。 使用温度范围: □□℃ - 200℃ 热时间常数: 小F8秒(逐汽中)



Type: TXW-064 Features:

Temp. sensor with movable probe head. Applications: Food processor or bread maker. Temperature Range: -0°C ~ 200°C

Thermal time constant : Less than 3sec. (in steam) 类型: TXW-064 特点: 头部可自由伸缩的温度传感器。

用途: 料理器及面包机等用。 使用温度范围: -10℃~200℃ 热时间常数: ≤小于3秒 (蒸汽中)



#### Type: TXW-065

Features: Temp. sensor with stainless steel tube encapsulated. Available for earth wire assembling.

Applications: IH high pressure cooker. Temperature Range: -10°C - 200°C

Thermal time constant : Less than 8sec. ( in steam)

#### 类型:TXW-065 特点: 不锈网保护管封装的温度传感器,可安装 接地线。

用途: 旧电压力电饭煲锅顶温度传感器。 使用温度范围: -10℃-200℃ 热时间常数:

热时间常数: 小于8秒(蒸汽中)